



Two / Four Ports Voice Gateway

# AG-268 / AG-468



## Product Overview

AG-268 and AG-468 gateways are Internet Telephony adapters offering 2 x FXS ports (AG-268) and 4 x FXS ports (AG-468)

A regular analog telephone can connect to AG-268 / AG-468 and establish voice communication over the internet or a private IP network.

The compact design and ease of installation of the AG-268 and AG-468 make it ideal for taking advantage of the many features made possible by VoIP technology.



## Key Features

- SIP v2.0 (RFC 3261)
- Codec: G. 711, G.723.1, G.726 and G.729A/B.
- Hybrid echo cancellation G.168 (16 ms)
- Auto switch between Fax and voice
- DTMF tone detection/regeneration
- Comfort Noise Generation (CNG)
- User programmable Call Progress detection/generation
- Voice Activity Detection (VAD)
- Facsimile protocol (option): T.30/T.38
- Real-time fax over IP
- DTMF tone detection/regeneration
- HTTP Server TFTP and flash memory for remote software download and upgrade
- VLAN Support
- SNMP (Simple Network Management Protocol)
- PPPoE
- TFTP
- HTTP

## Hardware Specification

Voltage: DC 9-24V

Power adapter: DC 12V/800mA

Network interface: (AG-268) 2 x RJ-45 Ethernet connectors  
(AG-468) 1 x RJ-45 Ethernet connector

Phone interface: (AG-268) 2 x RJ-11  
(AG-468) 4 x RJ-11

Dimension: 150 x 110 x 28 mm (L x W x H)



76 Sukhumvit Soi 2  
Klongtoey, Bangkok  
Thailand 10110

Tel: 02-656-8597

Fax: 02-250-9769

E-mail: sales@poisetech.com

