



11g Wireless Access Point



WAP-3000

H/W Version: 1

Product Overview

The LevelOne WAP-3000 11g Wireless Access Point acts as a bridge between wired Ethernet and Wireless 11b/g networks for wireless clients to access available wired and wireless networks.

Multiple Operation Modes

The WAP-3000 supports AP, AP Client, WDS bridging and Repeater wireless operation modes for flexible deployment and use within a standard Local Area Network. For standard operations, the WAP-3000 connects to a LAN, broadband ADSL router or network switch and provides instant network access to connected wireless clients. With WDS+AP mode the WAP-3000 is able to act as a bridge between two or more networks, combining them into a single network to provide wireless users with

access to both networks. In Repeater mode, the WAP-3000 extends the wireless area network to different locations.

Robust Wireless Security

The WAP-3000 provides 64/128-bit WEP encryption as well as WPA, WPA2 secured connectivity for securing the Wireless Area Network and to prevent unauthorized access.

Plug-and-Play Expansion of Home/Office Network

The LevelOne WAP-3000 Wireless AP is an easy to install "plug-and-play" access point with an easy to use Web-based user interface. The WAP-3000 requires little set-up and configuration and features an LED display for quick monitoring of network errors and activity.



1. LED Indicators
2. Reset Button
3. LAN Interface
4. Power Port

Key Features

- IEEE 802.11b/g compliant Wireless Access Point suitable for extending an existing LAN
- Features a 1-port Fast Ethernet interface
- Provides a wide area coverage range
- Features WPA, WPA2, 64/128-bit WEP encryption for a secured wireless network
- Supports multiple wireless operation modes
- Full LED display panel for error detection and network monitoring
- Compact design for desktop or wall-mounting
- Plug-and-Play enabled for easy setup and configuration
- Web-based configuration interface

Works Well With



WNC-0305USB
54 Mbps Wireless USB Adapter



WPC-0301
11g Wireless CardBus Card

Technical Specification

Standards

IEEE 802.11g, IEEE 802.11b

Network Interface

1x10/100Mbps LAN

Radio Operation

Data Transfer Rate

802.11g: up to 54Mbps

802.11b: up to 11Mbps

Modulation

802.11g: OFDM

802.11b: CCK, QPSK, BPSK

Media Access Control

CSMA/CA with ACK

Frequency Band

2.4GHz ~ 2.4835GHz

Number of Channels

Channel 1 ~ 11 North America

Channel 1 ~ 13 Europe, Japan

Antenna

1 x 2dBi external detachable dipole

Receiver Sensitivity(Typical)

802.11g: 10% PER, -68 dBm @ 54Mbps

802.11b: 8% PER, -81 dBm @ 11Mbps

Transmitter Output Power(Typical)

802.11g: 15dBm

802.11b: 18dBm

Operation Range

Indoor: approx.up to 50 meters

Outdoor: approx.up to 100 meters

Operation Mode

- AP mode
- AP Client mode
- Bridge mode
- Multiple bridge mode
- Repeater mode

Network Security

- WEP-64/128 bit

- WPA

- WPA-PSK

- WPA2

- WPA2-PSK

- Disable SSID Broadcast

- MAC address filtering

Management

- Web-based configuration

- OS Supported: Windows 2000/XP/Vista

Physical Specifications

LED

- Power

- LAN

- WLAN

Power Adapter

DC 7.5V, 1A

Temperature

Operating: 0 ~ 40°C

Storage: -25 ~ 70°C

Humidity

10% ~ 95% (Non-condensing)


Dimensions

146mm (L) x 113mm (W) x 32mm (H)

Certifications

CE,FCC

Product Diagram



Order Information

WAP-3000: 11g Wireless Access Point

Package Content

WAP-3000

Power Adapter

Antenna x 1

LAN Cable

Quick Installation Guide

CD Manual