



netis®

Easy Network, Trustable

Beacon N300 Gaming Router

WF2631



Features:

>Automatically enable QoS to secure 80% online bandwidth to enhance your gaming experience

>Include your favorite game into the Gaming Library for the Beacon Router to automatically enable QoS when playing

>WPS Button for One Button Security Setup

>Multiple Wireless Modes: AP, WDS, AP+WDS, Client, Repeater Modes

Brief:

The Netis WF2631 Beacon Series Wireless N300 Router takes your gaming experience to the next level! Offering a powerful performance by automatically activating QoS to enhance your online gaming experience. Bundled with three 5dBi high gain antennas, it ensures a wider & stronger wireless coverage. Allowing you to enjoy the wireless freedom anywhere around your home.

Specification:

Wireless

Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n		
Signal Rate	Up to 300Mbps		
Frequency Range	2.4-2.4835GHz		
Transmit Power	20dBm(MAX)		
Data Transfer Rate	802.11n: 40MHz(150Mbps, 135Mbps, 120Mbps, 90Mbps, 60Mbps, 45Mbps, 30Mbps, 15Mbps) 20MHz(72Mbps, 65Mbps, 57Mbps, 43Mbps, 28Mbps, 21Mbps, 14Mbps, 7Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)		
Wireless Modes	AP, Repeater, AP+WDS, WDS, Client		
Wireless Security	64/128-bit WEP WPA-PSK/WPA2-PSK(TKIP/AES) SSID Broadcast Enable/Disable		

Hardware

Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX		
Interface	1 * 10/100Mbps Auto MDI/MDIX RJ45 LAN port	4 * 10/100Mbps Auto MDI/MDIX RJ45 LAN port	
LED Indicators	PWR, WLAN, LAN1-LAN4, WAN, WPS		
Button	Default, WPS		
Antenna	3* 5dBi Fixed Antenna		
Power Supply	DC 9V/500mA(Output)		

Software

LAN Type	DHCP, Static IP, PPPoE, L2TP, PPTP, WISP		
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port		
QoS	WMM, Bandwidth Control for gaming mode		
Access Control	IP/MAC/Domain Filtering		
VPN Pass-through	PPTP, L2TP, IPSec		
Others	Client Software for Gaming QoS, Multiple SSID, Dynamic DNS, Static Routing		

Others

Certification	FCC, CE		
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing		
Package	1 * WF2631 1 * 9V/500mA Power Adapter 1 * Installation CD (for Client Software) 1 * Ethernet Cable 1 * Cradle 1 * Quick Installation Guide		