



300Mbps

Wireless N DOCSIS 3.0 Cable Modem Router

TC-W7960

Highlights


- 300Mbps Wi-Fi – wireless speeds provides a ultra-wireless experience
- 343 Mbps for Downstream – Download speeds up to 343Mbps and upload speeds up to 143Mbps for a fast, responsive Internet connection
- 8x Faster Downloads – DOCSIS 3.0 technology delivers speeds 8x faster than DOCSIS 2.0
- 4 Gigabit Ports – 4 Gigabit Ethernet ports ensure ultra-high wired performance
- 1 USB 2.0 port – Access files & media from networked devices or remotely via FTP server and share a printer locally
- IPV6 – Support IPv4 and IPv6 simultaneously
- Easy Setup – Quick, hassle-free installation
- Eliminate Monthly Rental Fees – Save money by returning your Internet service provider's rental modem router
- Compatible with major cable ISPs – XFINITY from Comcast, Time Warner Cable and more




300Mbps
2.4GHz



DOCSIS 3.0
343Mbps




Gigabit
Ports



USB
2.0 Port



Guest
Network



Parental
Control

Features



Speed

- **300Mbps Wi-Fi** – wireless speeds provides a ultra-wireless experience
- **343 Mbps for Downstream** – Download speeds up to 343Mbps and upload speeds up to 143Mbps for a fast, responsive Internet connection
- **8x Faster Downloads** – DOCSIS 3.0 technology delivers speeds 8x faster than DOCSIS 2.0



Efficiency

- **Eliminate Monthly Rental Fees** – Save money by returning your Internet service provider's rental modem
- **Compatible with major cable ISPs** – XFINITY from Comcast, Time Warner Cable and more
- **Compatibility** – Backwards-compatible with existing DOCSIS 1.0, 1.1, and 2.0 systems



Reliability

- **4 Gigabit Ports** – 4 Gigabit Ethernet ports ensure ultra-high wired performance
- **1 USB 2.0 port** – Access files & media from networked devices or remotely via FTP server and share a printer locally
- **IPV6** – Support IPv4 and IPv6 simultaneously



Ease of Use

- **Easy Setup** – Quick, hassle-free installation
- **Well-defined LEDs** – Clearly display device and network status




Security

- **Guest Network** – Guest Network provides secure Wi-Fi access for guests
- **Parental Control** – Establish restricted access policies for all connected devices
- **Security** – Supports BPI/BPI+/SEC

Specifications


Hardware Features

- Memory: 16 MB flash and 128MB DDR3 SDRAM
- Interface: 4 10/100/1000Mbps RJ45 LAN Ports 1 Coax Port 1 USB 2.0 Port
- Button: 1 Power On/Off Button 1 WPS Button 1 Wi-Fi On/Off Button 1 Reset Button
- External Power Supply: 12VDC/1.5A
- IEEE Standards: IEEE802.3, 802.3u, 802.3ab, 802.1q
- DOCSIS Standards: DOCSIS® 1.0, 1.1, 2.0, & 3.0
- Dimensions (W x D x H): 8.17 x 5.48 x 2.87 in. (207.5 x 139.1 x 72.8mm)
- Antenna Type: 2 Internal Antennas



Wireless Features

- Wireless Standards: IEEE 802.11n/g/b 2.4GHz
- Wireless Speeds: Up to 300Mbps
- Frequency: 2.4GHz
- Transmit Power: <30dBm(EIRP)
- Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless MAC Filtering
- Wireless Security: Support 64/128 bit WEP, WPA /WPA2, WPA-PSK/WPA2-PSK



Specifications

Software Features

- **Security:** NAT Firewall, Access Control
- **IPv6:** IPv6 and IPv4 dual stack
- **Management:** Web Based Configuration(HTTP), Remote management, SSL for TR-069, SNMP v1/v2/v3, Diagnostic Tools
- **DHCP:** Server, Client, DHCP Client List
- **NAT:** Port Forwarding, Port Triggering, UPnP, DMZ, ALG
- **Dynamic DNS:** DynDns, NO-IP
- **VPN Passthrough:** PPTP, L2TP, IPSec Passthrough
- **Advanced Functions:** Parental Control, MAC/IP/URL Filtering; RIP v1/v2 (optional); DNS Relay, DDNS, IGMP V1/V2/V3
- **USB Sharing:** Storage Sharing, FTP Server, Media Server, Print Server
- **Guest Network:** 2.4GHz guest network × 1

Others

- **Operation System:** Windows 8/Windows 7/ Windows Vista™, Service Pack 1 or later/ Windows®XP, Service Pack 2 or later/ Mac®10.4 or later (Ethernet connection only) UNIX®Linux®
- **Certification:** FCC, UL, CableLabs certified, RoHS compliant
- **Environment:**
 - **Operating Temperature:** 0 °C ~40 °C (32 °F ~104 °F)
 - **Storage Temperature:** -30 °C ~70 °C (-22 °F ~158 °F)
 - **Operating Humidity:** 5%~95% non-condensing
 - **Storage Humidity:** 5%~95% non-condensing
- **Package Contents:** TC-W7960, Ethernet Cable, Power Adapter, Quick Installation Guide, Information Card, Technical Support

Others

Ideal to use with



- AC1200 Wireless Dual Band USB Adapter Archer T4U



- AC600 Wireless Dual Band USB Adapter Archer T2U

Similar Products



- DOCSIS 3.0 Cable Modem TC-7610



- AC1750 Wireless Dual Band DOCSIS 3.0 Cable Modem Router Archer CR700



For more information, please visit

http://www.tp-link.com/en/products/details/cat-16_TC-W7960.html

or scan the QR code left

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies CO., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

www.tp-link.com